

## Victoria Scissor Lift License

Victoria Scissor Lift License - There is an inherent risk in operating a scissor lift, because with all types and kinds of powered work tools would require right handling in order to prevent accidents which could result in injuries or damage. Companies must make certain that personnel utilizing this particular equipment have the necessary experience.

Businesses must not allow scissor lifts to be utilized by untrained people. The scissor lift is used to lift people to high levels. Failure to understand and fully follow safety standard could lead to injuries for the users or damage to the lift.

For those who use scissor lifts, there is no legislation governing the use of fall protection. Nevertheless, manufacturers could suggest the use of fall protection and in some cases tying off in scissor lifts might be required by employer guidelines, local regulations or job-specific risk assessment.

Prior to using the machine, the scissor-lift operator needs to perform a thorough check in order to ensure the machine is in good working order. This is the operator's task, even though the unit has already been in service that day. The equipment's operator's instruction manual contains a pre-operation checklist.

The things that an operator must look for when doing a scissor lift check, includes checking tire-inflation pressure, and checking ground controls and platform controls in order to ensure they are functioning. Look for any delayed movement on the fly section when the boom is retracting and extending as this can indicate some cables are loose. When operating the controls, make certain that the emergency stop switches work. Operate functions against the equipment's cutout switches. Check the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters must stop the unit automatically before it moves into an unstable position, if they are working correctly. If they aren't, shut down the lift and make certain that it is fixed before it is utilized again.

Proper and safe operating procedures should be followed always. Levers must be operated with even, controlled pressure. A control lever must never be pushed from one position to the opposite position. The lever should be shifted to neutral, before stopping, and after that proceeding in the desired direction. When released, levers and control switches must return to the neutral position automatically. Depress the foot switch before operating platform controls.